

4 SPECIFICATIONS | DIMENSIONS

| | |
|---------------------|--------------------------------|
| Line input: | Balanced, 10kOhm, + 20dBu max, |
| Frequency response: | 20Hz up to 20kHz |
| Output: | Balanced, 120 Ohm, + 4 dBu max |
| GPO: | Opto Fet 60V/550Ma, Pmax=500mW |
| GPI: | Pulldown to GND. |
| Tip: | uses opto coupler. |
| Frequency band: | 2.4 GHz band |
| Antenna: | Built in |

DIMENSIONS/WEIGHT

| | |
|------------------|---------|
| Left-Right: | 90mm |
| Front to back: | 110mm |
| Height: | 32-38mm |
| Front thickness: | 2mm |

| | |
|-----------------|--|
| Weight: | 0.50 kg |
| Power: | 90-240volt 50/60Hz |
| Voltage: | 12Vdc provided by mains adapter (included) |
| Supply Current: | < 0.5 Amp |

We wish you many creative years of productivity using this quality product from:

| | |
|----------|---|
| Company | : D&R Electronica B.V. |
| Address | : Rijnkade 15B |
| Zip Code | : 1382 GS |
| City | : WEESP |
| Country | : Netherlands |
| Phone | : 0031 (0)294-418 014 |
| Website | : http://www.dnrbroadcast.com |
| E-mail | : support@d-r.nl |